

What is claimed is:

1. An optical element having a substrate formed by an optical material,

said substrate comprising:

5 a convex part functioning as a convex lens;
a flat part positioned around said convex part;
and

an outer circumference part positioned around said flat part, wherein

10 a thickness of said outer circumference part is greater than that of said flat part,

whereby the mechanical strength is improved and the resonance frequency is increased.

2. An optical element as set forth in claim 1,
15 wherein the thickness of said outer circumference part is greater than that of said convex part.

3. An optical element as set forth in claim 1,
wherein said substrate comprises a first groove formed at a boundary between said convex part and said flat part,
20 for defining a region of said convex part.

4. An optical element as set forth in claim 3,
wherein said substrate comprises a second groove formed at a boundary between said flat part and said outer circumference part, for defining a region of said flat
25 part.

09933151 052101
10220 15250

5. An optical element as set forth in claim 1,
wherein said optical material comprises fused silica.

6. An optical element as set forth in claim 1,
wherein a surface of said outer circumference part is
5 flat or approximately flat and thereby holding is eased.

7. An optical element as set forth in claim 1,
wherein a plurality of steps are formed at said outer
circumference part, the thickness of said substrate at an
outer side step is thicker than that of said substrate at
10 an inner side step, and thereby eclipse is prevented.

8. An optical element having a substrate formed by
an optical material,

said substrate comprising:

a convex part functioning as a convex lens;
15 a flat part positioned around said convex part;
an outer circumference part positioned around
said flat part;

a first groove formed at a boundary between
said convex part and said flat part, for defining a
20 region of said convex part; and

a second groove formed at a boundary between
said flat part and said outer circumference part, for
defining a region of said flat part, wherein

a thickness of said outer circumference part is
25 greater than that of said flat part;

both said flat part and said outer
circumference part comprise flat shapes in the thickness
direction; and

said convex part, said flat part, and said
5 outer circumference part are integrated in a unit by said
substrate.

9. An optical element having a substrate formed by
an optical material,

said substrate comprising:

10 a convex part functioning as a convex lens;
a flat part positioned around said convex part;
an outer circumference part positioned around
said flat part; and

a groove formed at a boundary between said
15 convex part and said flat part, for defining a region of
said convex part, wherein

a thickness of said outer circumference part is
greater than that of said convex part;

both said flat part and said outer
20 circumference part comprise flat shapes in the thickness
direction; and

said convex part, said flat part, and said
outer circumference part are integrated in a unit by said
substrate.

25 10. An optical element having a substrate formed by

an optical material,

said substrate comprising:

a convex part functioning as a convex lens;

a flat part positioned around said convex part;

5 a first outer circumference part positioned
around said flat part;

a second outer circumference part positioned
around said first outer circumference part;

10 a third groove formed at a boundary between
said convex part and said flat part, for defining a
region of said convex part; and

a fourth groove formed at a boundary between
said flat part and said first outer circumference part,
for defining a region of said flat part, wherein

15 a thickness of said first and second outer
circumference parts are greater than that of said flat
part and the thickness of said second outer circumference
part is greater than that of said first outer
circumference part;

20 all said flat part and said first and second
outer circumference parts comprise flat shapes in the
thickness direction; and

said convex part, said flat part, and said
first and second outer circumference parts are integrated
25 in a unit by said substrate.

09933454 093404

5 formed by an optical material;

etching said substrate to transfer said convex lens shape of said first mask layer to said substrate.

15 13. A method for producing an optical element as set forth in claim 11, wherein, in the step for heat treating said first mask layer to form it into a convex lens shape, the heat treatment temperature is higher than a glass transition temperature of said first mask layer.

25 15. A method for producing an optical element as

said first mask layer is formed by an optically transparent material having a good characteristic for forming a thick film, and

said second mask layer is formed by platinum.

5 19. A method for producing an optical element as set forth in claim 17, wherein

said third mask layer is formed by platinum and

said fourth mask layer is formed by an

10 optically transparent material having a good characteristic for forming a thick film.

20. An optical pickup comprising:

an optical element functioning as an object lens when mounted on a recording and/or reproducing apparatus of an optical storage medium and

15 a photodetector for receiving a reflected light beam for use in recording and/or reproduction to and from the optical storage medium,

the optical element comprising a substrate formed by an optical material,

20 the substrate comprising

a convex part functioning as a convex lens,

a flat part positioned around the convex part,

and

25 an outer circumference part positioned around the flat part,

00933151 082401
101280 195550

a thickness of the outer circumference part being thicker than that of the flat part to thereby improve mechanical strength and increase a resonance frequency.

5 21. An optical pickup as set forth in claim 20,
wherein the thickness of said outer circumference part is greater than that of said convex part and thereby the mechanical strength of said optical element is improved and the resonance frequency of said optical element is
10 increased.

22. An optical pickup as set forth in claim 20,
wherein a surface of said outer circumference part is flat or approximately flat and thereby holding of said optical element is eased.

15 23. An optical pickup as set forth in claim 20,
wherein a plurality of steps are formed at said outer circumference part, the thickness of said substrate at an outer side step is greater than that of said substrate at an inner side step, and thereby eclipse is prevented.

05033451.052404
TOP SECRET